

AS 2600

Mehrfachverriegelung mit Hauptschloss und 2x Bolzen-Schwenkhaken-Kombination
25 und 30 mm Dorn = AS 9600

Art. Nr.	Stulp	Maße
AS 2600 F 16		16 x 3 mm
AS 2600 F 20		20 x 3 mm
AS 2600 F 24		24 x 3 mm
AS 2600 P 6/24		6 x 24 x 6 x 2 mm
AS 2600 P 8/24		8 x 24 x 8 x 2 mm Niro
AS 2600 P 10/24		10 x 24 x 10 x 2 mm Niro
AS 2600 P 6/22		6 x 22 x 6 x 2 mm
AS 2600 P 8/22		8 x 22 x 8 x 2 mm Niro
AS 2600 P 10/30		10 x 30 x 10 x 2 mm

Entfernung	Dornmaß in mm												
 92	-	-	-	35	40	45	50	55	-	65	70	80	- 100
	-	-	-	20	20	20	20	20	-	20	20	20	- 20
	8 mm, 10 mm												

Varianten in mm							
		A	B	C	G	I	K
92 mm	B001	2170	760	730	1020	290	130
	B002	2170	760	730	1050	260	160
	B003*	2400	760	980	1020	270	130
	B004*	2400	760	980	1050	240	160
	B291	2170	635	480	1020	540	255
	B296	2170	760	355	1020	665	130
	B298	2170	760	605	1020	415	130
	B325	2170	760	355	1050	635	160
	B327	2170	760	605	1050	385	160
	K002	1754	760	730	892	-	-

* Gilt nur bei Flachstulpen

